



**TOPAIR**  
CLEAN AIR SOLUTIONS

# DUCTLESS FUME HOODS



TOPAIR





# Ductless Fume Hood EN-14175 / ASHRAE 110

## Ductless Fume Hood

TopAir's polypropylene Ductless Fume Hood provides a safe environment for lab staff working with a variety of chemicals.

Our Ductless Fume Hood offers an air velocity display and alarm with a full Variable Air Volume (VAV) automatic speed adjustment to meet  $100 \pm 20$  fpm ( $0.5 \pm 0.1$  m/s).

This model is also equipped with a chemical VOC sensor and alarm to detect high levels of volatile compounds present in the filter for extra safety.

TopAir's Ductless Fume Hoods can be customized to meet size requirements as needed.

### Structure:

- 8 mm welded polypropylene with high chemical resistance
- Built-in sealed polypropylene worktop or choice of epoxy, stainless steel, ceramic, or Trespa high pressure compact laminates (HPLs)
- 5 mm safety front glass window with sliding front sash with counterweight
- Side windows for better visibility



- 10.1" color touchscreen display
- VAV with air flow alarm and display
- VOC sensor and alarm
- Chamber alert light (red) for critical alarms
- High efficiency quiet ECM fan
- 800 lux LED lighting separated from the work area
- Adjustable air velocity  $100 \pm 20$  fpm ( $0.5 \pm 0.1$  m/s)
- Convenient front access for filter replacement
- Variety of HEPA filters, carbon filters, and pre-filters
- 10" (250 mm) exhaust point collar for connection to external exhaust
- Optional: metal stand or polypropylene base cabinet
- **Certifications: EN-14175 / ASHRAE 110-1995, CE**



# Ductless Fume Hood EN-14175 / ASHRAE 110

Spec/ Model	CF-060-PP	CF-090-PP	CF-120-PP	CF-150-PP	CF-180-PP
<b>Outer Dimensions W x D x H</b>	600 x 750 x 1223 mm 23.62 x 29.5 x 48"	900 x 750 x 1223 mm 35.4 x 29.5 x 48"	1200 x 750 x 1223 mm 47.24 x 29.5 x 48"	1500 x 750 x 1223 mm 59 x 29.5 x 48"	1800 x 750 x 1223 mm 70.8 x 29.5 x 48"
<b>Dimensions for XL model W x D x H For XL models add -XL to P/N</b>	600 x 750 x 1500 mm 23.62 x 29.5 x 59"	900 x 750 x 1500 mm 35.4 x 29.5 x 59"	1200 x 750 x 1500 mm 47.24 x 29.5 x 59"	1500 x 750 x 1500 mm 59 x 29.5 x 59"	1800 x 750 x 1500 mm 70.8 x 29.5 x 59"
WE CAN CUSTOMIZE TO ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS					
<b>Workspace (W x D x H)</b>	585 x 590 x 695 mm 23 x 23.2 x 27.3"	885 x 590 x 695 mm 34.8 x 23.2 x 27.3"	1185 x 590 x 695 mm 46.6 x 23.2 x 27.3"	1485 x 590 x 695 mm 58.4 x 23.2 x 27.3"	1785 x 590 x 695 mm 70.2 x 23.2 x 27.3"
<b>Front Sash Max. Opening</b>	495 mm / 19.5"				
<b>Test Standard</b>	Comply	EN-14175 / CE / ASHRAE 110-1995	EN-14175 / CE / ASHRAE 110-1995	EN-14175 & ASHRAE 110-1995	EN-14175 & ASHRAE 110-1995
<b>Air Velocity</b>	0.5±0.1 m/s, 100±20 fpm				
<b>Hood Material</b>	8mm welded white polypropylene structure with built-in sealed polypropylene worktop				
<b>Noise</b>	<52dB	<52dB	<54dB	<60dB	<62dB
(Tested 20 cm (8") from the worktable, 1.2m (48") above ground)					
<b>Power Supply</b>	110/220 V, 50/60 Hz, Single phase				
<b>Illumination</b>	800 lux, eco-friendly LED lighting				
<b>Available Filter</b>	Pre-filter & carbon filters for solvents, acids, bases, formaldehyde, multi gas (blend of materials) / HEPA				

## Optional accessories:

- XL model with 2 internal filters
- Metal stand with casters
- Polypropylene base cabinet
- UV light
- Gas taps
- Water taps
- Polypropylene cup sink
- Polypropylene sinks
- Electrical outlets
- Clear back for educational purposes





# Valueline Ductless Fume Hood

## Valueline Ductless Fume Hood

TopAir's Valueline Ductless Fume Hood provides a safe environment for lab staff working with a variety of chemicals.

This cost-effective benchtop ductless fume hood with an innovative, intelligent control system includes a 7" color touchscreen with airflow monitoring, alarm, integral polypropylene worktop, a sliding front sash with counterweight, an environmentally friendly EC fan, and LED light.

A variety of filters can be supplied for maximum protection from most common chemical fumes.

TopAir's Value-line Ductless Fume Hoods can be customized meet size requirements as needed.

### Structure:

- 8 mm welded Polypropylene with high chemical resistance
- Built-in sealed polypropylene worktop
- 5 mm safety front glass window with sliding front sash with counterweight
- Side windows for better visibility



- 7" color touchscreen display
- Airflow display and alarm
- 10 speed fan control
- Chamber alert light (red) for critical alarms
- Built-in sealed polypropylene worktop
- Tempered glass side windows and sliding front sash with counterweight
- 800 lux LED lighting
- Air velocity  $100 \pm 20$  fpm ( $0.5 \pm 0.1$  m/s)
- Back access for filter replacement
- Variety of HEPA and carbon filters
- EC fan with 10 levels of speed adjustment
- 10" (250 mm) exhaust collar for connecting to external exhaust
- Optional: metal stand or polypropylene base cabinet
- **Certification: CE**



# Valueline Ductless Fume Hood

Spec/ Model	VL-CF-060-PP	VL-CF-090-PP	VL-CF-120-PP
Outer Dimensions (W x D x H)	750 x 630 x 1050 mm 29.5 x 24.8 x 41.3"	900 x 630 x 1050 mm 35.4 x 24.8 x 41.3"	1200 x 630 x 1050 mm 47.2 x 24.8 x 41.3"
Workspace (W x D x H)	730 x 450 x 550 mm 28.7 x 17.7 x 21.6 "	880 x 450 x 550 mm 34.6 x 17.7 x 21.6 "	1180 x 450 x 550 mm 46.4 x 17.7 x 21.6 "
Max Sash Working height	500 mm / 19.7"		
Microprocessor control	7" touch screen with airflow alarm, 10-speed fan control, filter replacement alarm, service alarm, lights control		
Air Velocity	0.5±0.1 m/s, 100±20 fpm		
Hood Material	Welded white polypropylene structure with built-in sealed polypropylene worktop		
Noise Level (Tested 20cm/8" from the worktable, 1.2m/48" above ground)	<52dB	<55dB	<57dB
Power Supply	110/220 V, 50/60 Hz, single phase		
Illumination	800 lux, eco-friendly LED lighting		
Filter	Carbon filters for solvents, acids, bases, formaldehyde, multi-gas (a blend of materials) /HEPA/ULPA		

## Optional accessories:

- Metal stand
- Gas and water taps
- Clear back for educational purposes



## Eco Ductless Fume Hood

TopAir's Ecoline Ductless Fume Hood provides a safe environment for lab staff working with acids and harsh chemicals.

This is the most cost-effective model of TopAir's ductless fume hoods product line, with an analog on/off control system, speed adjustable EC fan, and LED light.

Suitable for simple applications, educational uses, and small labs, it is a lightweight benchtop cabinet (metal stand is optional) with a small footprint.

### Structure:

- 8 mm welded Polypropylene structure with high chemical resistance
- Built-in sealed polypropylene
- Tempered glass partial sliding front sash with a max working height of 8" (200 mm)
- Analog control on/off system

Manual Analog on/off system with fan speed adjuster

- 600 lux LED lighting
- Adjustable air velocity:  $100 \pm 20$  fpm ( $0.5 \pm 0.1$  m/s)
- Variety of HEPA and carbon filters
- ECM fan
- CE certified, complies with AFNOR NF X 15-211: 2009 standard



# Eco Ductless Fume Hood

Spec/ Model	ECO-CF-075	ECO-CF-090	ECO-CF-120
<b>Outer Dimensions (W x D x H)</b>	750 x 520 x 840 mm 29.5 x 20.4 x 33"	900 x 520 x 840 mm 35.4 x 20.4 x 33"	1200 x 520 x 840 mm 47.2 x 20.4 x 33"
<b>Workspace (W x D x H)</b>	735 x 400 x 450 mm 28.9 x 15.7 x 17.7"	885 x 400 x 450 mm 34.8 x 15.7 x 17.7"	1185 x 400 x 450 mm 46.6 x 15.7 x 17.7"
<b>Equipment Entry Opening</b>	450 mm / 17.7"	450 mm / 17.7"	450 mm / 17.7"
<b>Fixed Sash Opening</b>	200 mm	200 mm	200 mm
<b>Air Velocity</b>	0.5±0.1 m/s, 100±20 fpm	0.5±0.1 m/s, 100±20 fpm	0.5±0.1 m/s, 100±20 fpm
<b>Hood Material</b>	Welded white polypropylene structure with built-in sealed polypropylene worktop	Welded white polypropylene structure with built-in sealed polypropylene worktop	Welded white polypropylene structure with built-in sealed polypropylene worktop
<b>Noise Level (Tested 20 cm from the worktable, 1.2m above ground)</b>	<60dB	<60dB	<60dB
<b>Power Supply</b>	110/220 V, 50/60 Hz, Single phase	110/220 V, 50/60 Hz, Single phase	110/220 V, 50/60 Hz, Single phase
<b>Illumination</b>	600 lux, eco-friendly LED lighting	600 lux, eco-friendly LED lighting	600 lux, eco-friendly LED lighting
<b>Filter</b>	Carbon filters for solvents /HEPA	Carbon filters for solvents /HEPA	Carbon filters for solvents /HEPA



# Ductless Walk-In Fume Hood

## Ductless Walk-In Fume Hood

TopAir's polypropylene Ductless Walk-In Fume Hood provides a large front opening designed to contain large, heavy, or tall equipment. The hood provides a safe environment for lab staff working with a variety of chemicals.

The hood offers a full variable air volume (VAV) system with automatic air velocity adjustment and airflow alarm to detect high levels of chemical concentration in the filters for extra safety.

### Structure:

- 8 mm welded polypropylene with high chemical resistance
- 5 mm safety glass vertical front sash or horizontal front doors (based on unit size)
- 10.1" color touchscreen display

TopAir's polypropylene Ductless Walk-In Fume Hood can be customized to meet size requirements as needed.

- Variable Air Volume (VAV) with automatic speed adjustment up to  $100\pm 20$  fpm ( $0.5\pm 0.1$  m/s)
- Air velocity display and alarm
- Chamber alert light (red) for critical alarms
- High efficiency quiet EC fan
- 800 lux LED lighting separated from the work area
- VOC sensor and alarm
- Variety of HEPA and carbon filters
- Exhaust point for connecting a second filter or an external exhaust.
- Optional vertical or horizontal sliding sash system
- **CE certified**

## Walk-In with Horizontal Doors





# Ductless Walk-In Fume Hood

Spec/ Model	CF-120-WI-PP	CF-150-WI-PP	CF-180-WI-PP	CF-200-WI-PP	CF-250-WI-PP
<b>Outer Dimensions for standard model W x D x H</b>	1200 x 830 x 2420 mm 47.3 x 32.6 x 95.3"	1500 x 830 x 2420 mm 59.0 x 32.6 x 95.3"	1800 x 830 x 2420 mm 70.8 x 32.6 x 95.3"	2000 x 830 x 2420 mm 78.7 x 32.6 x 95.3"	2500 x 830 x 2420 mm 98.4 x 32.6 x 95.3"
<b>WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS</b>					
<b>Workspace (W x D x H)</b>	1000 x 530 x 1800 mm 39.4 x 20 x 70.9"	1300 x 530 x 1800 mm 21 x 20 x 70.9"	1600 x 530 x 1800 mm 63 x 20 x 70.9"	1800 x 530 x 1800 mm 70.8 x 20 x 70.9"	2300 x 530 x 1800 mm 90.5 x 20 x 70.9"
<b>Front Sash Max. Opening</b>	1600 mm / 63"				
<b>Air Velocity</b>	0.5±0.1 m/s, 100±20 fpm				
<b>Hood Material</b>	(Tested 20 cm from sash line and 1.2m above ground) Welded white polypropylene structure with built-in sealed polypropylene worktop				
<b>Power Supply</b>	110/220 V, 50/60 Hz, single phase				
<b>Illumination</b>	800 lux, eco-friendly LED lighting				
<b>Filter</b>	Carbon filters for solvents, acids, bases, formaldehyde, multi gas (blend of materials) /HEPA/ULPA				

## Optional accessories:

- XL model with 2 internal filters
- clear back for educational purposes

## Walk-In with vertical sash





# Polypropylene Hybrid Laminar Airflow Ductless Fume Hood

TopAir's Laminar Airflow Ductless Fume Hoods combine the functionality of ductless fume hoods and laminar clean benches.


The product is equipped with dual filtration system:

1. Supply system with a pre-filter, HEPA filter and a fan that creates laminar down-flow towards the working area.
2. Exhaust system with carbon filter and fan that collects the down-flow and creates protective inflow on the front sash opening. Both inflow and down flow pass through the carbon filter before the air is exhausted back into the lab.

### Structure :

- 8 mm welded polypropylene with high chemical resistance
- Double back wall with baffle
- Built-in sealed polypropylene or optional stainless steel worktop
- Tempered glass, full-opening sliding front sash with counterweight
- Extraction collar for external exhaust

- 10.1" color touchscreen display
- VAV with air flow alarm and display
- Automatic laminar air velocity, manual adjustment for inflow includes a safety shutdown system for the down-flow when inflow system fails
- VOC sensor and alarm
- Chamber alert light (red)
- Cleanliness level: Class 100/ISO 5
- 800 lux LED lighting separated from the work area
- Includes polypropylene lower base cabinet
- **CE certified**



# Polypropylene Hybrid Laminar Airflow Ductless Fume Hood

Spec/ Model	CF-120-HCV	CF-150-HCV	CF-180-HCV	CF-200-HCV	CF-250-HCV
<b>Outer Dimensions for standard model W x D x H</b>	1200 x 850 x 2420 mm 47.3 x 33.4 x 95.2"	1500 x 850 x 2420 mm 59.0 x 33.4 x 95.2"	1800 x 850 x 2420 mm 70.9 x 33.4 x 95.2"	2000 x 850 x 2420 mm 78.7 x 33.4 x 95.2"	2500 x 850 x 2420 mm 98.4 x 33.4 x 95.2"
<b>WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS</b>					
<b>PPS OPTION AVAILABLE!</b>					
<b>Workspace (W x D x H)</b>	1000 x 600 x 800 mm 39.4 x 23.6 x 31.5"	1300 x 600 x 800 mm 51.2 x 23.6 x 31.5"	1600 x 600 x 800 mm 63 x 23.6 x 31.5"	1800 x 600 x 800 mm 70.8 x 23.6 x 31.5"	2300 x 600 x 800 mm 90.5 x 23.6 x 31.5"
<b>Front Sash Max. Opening</b>	600 mm / 23.6"				
<b>Sash Working Height</b>	300 mm / 12"				
<b>inflow</b>	0.5±0.1 m/s, 100±20 fpm				
<b>Down flow</b>	0.33±0.1 m/s, 66±10 fpm				
<b>Hood Material</b>	8mm welded white polypropylene structure with built-in sealed polypropylene worktop				
<b>Cleanliness Level</b>	Class 100/IOS 5				
<b>Work Table</b>	Polypropylene / Stainless steel				
<b>Control System</b>	VAV System with 10.1" color touch screen				
<b>Optional</b>	Water tap/ gas tap / vacuum tap/ polypropylene sink				
<b>Power Supply</b>	110 / 220V, 50/60 Hz, single phase				

## Optional accessories:

- Sinks
- Water tap
- Gas tap
- Vacuum tap
- Electric sockets



## Downflow Unit

TopAir's Downflow Workstation is a standalone ductless unit that protects lab staff from harmful particulate matter or fumes.

The Downflow Workstation features an open structure which enables easy access for lab personnel.

Particulate matter flows downward through the polypropylene work surface and contaminants are removed using a HEPA filter.

### Structure:

- 8 mm welded polypropylene with high chemical resistance
- Perforated retractable polypropylene worktop (stainless steel optional)

- Manual analog on/off system with fan speed adjustment
- Polypropylene worktop combined with a drawer for easy cleaning
- H14 HEPA filter
- High efficiency EC fan
- 800 lux LED lighting
- Optional: 395 nm UV light (black light)
- **CE certified**



## Downflow Unit

Spec/ Model	DF-60	DF-90	DF-120
<b>External Dimensions WxDxH</b>	60 x 70 x 120 cm 23.6 x 27.5 x 47.2"	90 x 70 x 120 cm 35 x 27.5 x 47.2"	120 x 70 x 120 cm 47.2 x 27.5 x 47.2"
<b>WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS</b>			
<b>Internal Height</b>	70 cm / 27.5"	70 cm / 27.5"	70 cm / 27.5"
<b>Power Supply</b>	115/230 V 50/60 Hz, Single phase	115/230 V 50/60 Hz, Single phase	115/230 V 50/60 Hz, Single phase
<b>Light</b>	LED 800 lux	LED 800 lux	LED 800 lux
<b>Worktop</b>	Polypropylene	Polypropylene	Polypropylene
<b>Structure</b>	Polypropylene	Polypropylene	Polypropylene
<b>Filter</b>	H14 HEPA	H14 HEPA	H14 HEPA
<b>Fan</b>	EC fan	EC fan	EC fan



# Weighing Station Kit for Ductless Fume Hood

## Weighing Station Kit

TopAir's Ductless Fume Hoods offer dual functionality by providing both fume containment and precise weighing capabilities.

The stable cabinets are designed for accurate measurements of powders and chemicals by delivering a weight precision up to four decimal places.

For enhanced weighing performance, an optional "weighing station kit" is available. This kit includes:

- HEPA filter
- Vacuum system for efficient residue collection

The HEPA filter removes powders and particles with an efficiency of 99.9995 @ 0.3 $\mu$ m and provides reassurance to the lab staff. The vacuum system is an excellent instrument to collect residues of powders from the working surface and channel them to the HEPA filter.

### Structure:

- Unit is based on the standard ductless unit (see pages 2-3)

Part Number : CF-W



# Educational Inverted Ductless Fume Hood PRO

TopAir's Inverted Educational Ductless Fume Hood with 360° glass provides an effective tool for educational purposes and a safe environment for lab staff working with acids and harsh chemicals.

The unit features an operating system with a 7" color touch screen to control the entire system including:

- Airflow alarm and display
- Chamber alarm (red)
- Light activation

### Structure:

- 8 mm welded polypropylene with high chemical resistance
- Double back wall with baffle
- Built-in sealed polypropylene worktop or choice of epoxy, stainless steel, ceramic, HPL
- Tempered glass, full opening sliding front sash with counterweight

- 7" Color touch screen display
- Air velocity display and alarm
- 360° Transparent glass
- High efficiency quiet ECM fan
- 800 lux LED lighting
- Convenient front access for filter replacement
- Educational carbon blend filter (22 kg) and pre-filter
- **Complies with BS7989:2001 and CLEAPSS**



Spec/ Model	CF-120-PRO-RV
Outer Dimensions W x D x H	1200 x 800 x 2270 mm 47.2 x 31.5 x 89.4"
WE CAN CUSTOMIZE ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS	
Workspace (W x D x H)	1160 x 600 x 1100 mm 45.7 x 23.6 x 43.3"
Front Sash Max	Min working height: 200 mm / Max working height: 350 mm
Test Standard	Compliance with BS7989:2001 and CLEAPSS
Air Velocity	Air flow display and alarm 0.5±0.1 m/s, 100±20 fpm
Hood Material	Welded white anti-corrosion polypropylene structure with built-in sealed polypropylene worktop
360 Visibility	360° visibility with 5 mm tempered safety glass / polycarbonate
Power Supply	110 / 220 V, 50/60 Hz, single phase
Illumination	800 lux, eco-friendly LED lighting
Filter	Activated carbon for a variety of chemicals and solvents. HEPA available

TOPAIR



**TOPAIR**  
CLEAN AIR SOLUTIONS

[www.topairsystems.com](http://www.topairsystems.com)

Tel : 1-855-6-TOPAIR / International: +1-855-686-7247

Headquarters: 300 First Avenue, Suite 102, Needham, MA 02494 USA

Email: [sales@topairsystems.com](mailto:sales@topairsystems.com)

